



GAMMA Series

GWT6-2A G-Build Engine

GWT6-2A 15, GWT6-2A 18

*Power range: 92.3–119.2 kW; 123.8–159.8 bhp
Fixed speed; full-load speed ranges: 1500 and 1800 r/min*


Turbocharged heavy-duty G-Build diesel engine

Special Attributes

- ✓ suitable for generating sets
- ✓ 400-hour service intervals
- ✓ continuous operation in ambient temperatures up to 45°C (113°F)
- ✓ cold-start down to -20°C (-4°F)

Basic Engine Characteristics

- six cylinders
- diesel fuelled
- direct injection
- liquid cooled
- turbocharged




Design Features and Equipment

- standard oil and fuel filters
- 12V electric start (optional 24V)
- anticlockwise rotation, looking on the flywheel
- SAE 10" and 11.5" flywheel
- SAE 3 flywheel housing
- radiator with fan guard
- cast-iron crankcase
- self-vent fuel system
- inline fuel injection pump
- flywheel with ring gear
- air cleaner
- low oil-pressure switch
- spin-on lubricating-oil filter
- fuel filter/agglomerator
- inlet and exhaust manifolds
- operators' handbook

Technical Data			
		GWT6-2A 15	GWT6-2A 18
Number of cylinders		6	
Firing order (number 1 cylinder is at gear end)		1 5 3 6 4 2	
Type of fuel injection		direct injection	
Aspiration		turbocharged	
Direction of rotation, looking on flywheel		anticlockwise	
Cylinder bore	mm	100	
	in	3.94	
Stroke	mm	127	
	in	5	
Total cylinder capacity	litre	5.99	
	in ³	365.2	
Compression ratio		17.5:1	
Rated maximum full-load speed	r/min	1500	1800
	m/sec	6.35	7.62
Mean piston speed	f/sec	20.8	25.0
Oil consumption		maximum 0.2% of fuel consumption	

Dimensions and Weight		
Length (A)	mm	1480
	in	58.3
Height (B)	mm	1108
	in	43.6
Width (C)	mm	716
	in	28.2
Dry Weight	kg	780
	lb	1719



Fuel Consumption		
r/min	1500	1800
litres/hour @ 100% power (continuous)	24.0	28.3

A comprehensive range of options allows you to select a specification that matches your requirements. Please ask your Lister Petter distributor. (See panel below left.)

Distributor's Address

Lister Petter have made efforts to ensure that the information in this data sheet is accurate but reserve the right to amend specifications and information without notice and without obligation or liability.

Power Outputs			
	r/min	1500	1800
Continuous Power	kW	92.3	108.4
	bhp	123.8	145.4
Overload Power	kW	102	119.2
	bhp	136.8	159.8

Rating Definitions, to ISO 3046

ISO Standard Conditions

Barometric pressure100 kPa
 Relative humidity..... 30%
 Ambient temperature at air inlet manifold25°C

Fixed speed power: continuous power (ICN)

The power in kW which the engine is capable of delivering continuously at the stated crankshaft speed, under ISO standard conditions, measured at the flywheel without power-absorbing accessories, provided that the engine is overhauled and maintained in good operating condition and that fuel to BS EN 590 Class A1 or A2, and lubricating oils to the correct performance specification and viscosity classification as recommended by Lister Petter Limited, are used.

Fixed speed power: overload power (ICXN)

The maximum power in kW which the engine is capable of delivering intermittently at the stated crankshaft speed for a period not exceeding one hour in any period of twelve hours' continuous running, immediately after working at the continuous power, under ISO standard conditions and with the provisions specified for continuous power above.

De-rating

For non-standard site conditions, reference should be made to relevant BS, ISO and DIN standards.

Notes:

1. Power ratings are measured at the flywheel end.
2. Power ratings and fuel consumption figures apply to a fully run-in, non-derated engine without a radiator and fan fitted, and without power-absorbing accessories or transmission equipment.



UK

Lister Petter Limited, Dursley, Gloucestershire
 GL11 4HS England

Tel: +44 (0)1453 544141; fax: +44 (0)1453 546732

E-mail: sales@lister-petter.co.uk <http://www.lister-petter.co.uk>